



ATF 7G LV

Description

A very high graded automatic transmission fluid formulated with a number of special selected base oils and additives to obtain the following properties:

- a high shifting comfort
- a very low pour point
- very good stability against oxidation
- very good thermal properties
- a positive activity against wear, corrosion and foam
- a constant friction stability over lifetime ensuring perfect clutch operation
- a perfect compatibility with seals and non-ferro metals
- extremely resistant against shudder vibration
- as a result of the perfect viscosity grade a fuel-efficiency potential
- without dye (available in red on request).

Application

This universal ATF with lower viscosity than conventional ATFs, can be used for automatic gearboxes of various car manufacturers, both in the low and high viscosity ATF segment that allow this. In addition to the specified specifications, this ATF is also applicable in certain types of automatic transmissions including: Bentley, Chrysler / Dodge / Jeep, Jaquar, Land Rover, Maserati and Porsche, for which a correspondingly low viscosity ATF is prescribed. This multi-purpose ATF also meets the hardware protection of specified ATF specifications for ultra low viscosity, but does not provide maximum fuel economy.

Specifications

Performance level:

- Aisin Warner JWS 33093324//AW-1, Allison C4
- Chrysler ATF+/+2/+3/+4
- GM Dexron ULV/VI/II/III/IV/IE/IIIG/IIIH/Suffix A
- Hyundai/Kia SP-II/III/IV/-IV RR/RED-1K/NWS 9638
- JASO M315 Type 1A LV, Mazda FZ/M-III/Type T-IV
- MB 236.12/236.14/236.15/236.17/236.41
- Nissan Matic D/J/K/S/W, Suzuki ATF 3314/3317
- Volvo 1161540, ZF TE-ML 11A/11B
- VW G 052 533 / G 052 990
- BMW 7045E/8072B/LA2634/LT71141/ATF3/3+/M-1375.4
- Ford Mercon ULV/LV/V/SP / WSS-M2C922-A1
- Honda DW-13.1/3.0//ATF-Z1 (except in CVT)
- Isuzu ATF II/III, Jaguar JLM 20238 / 20292 / 21044
- MB 236.5/236.6/236.7/236.8/236.9/236.10/236.11
- Mitsubishi SP-II/III/J2/J3/PA
- Subaru ATF HP, Toyota Type DII/T-T-III/T-IV/WS
- VW G 052 025 / G 052 055 / G 052 162
- VW G 055 005 / G 055 025 / G 055 540 / G 060 162

Typicals

Density at 15 °C, kg/l	0,857
Viscosity 40 °C, mm ² /s	27,40
Viscosity 100 °C, mm ² /s	6,37
Viscosity Index	197
Flash Point COC, °C	146
Pour Point, °C	-57