

ATF VI

Description

A very high graded automatic transmission fluid based on special selected synthetic base oils, with a high viscosity index and a number of selected additives to obtain the following properties:

- a very strong dispersion, therefore sludge is restricted to a minimum
- a very low pour point
- very good stability against oxidation and thermal properties
- a positive activity against wear, corrosion and foam
- specific friction properties
- a perfect compatibility with seals and non-ferro metals
- red coloured.

Application

This fluid may be used for automatic gear boxes (including hybrid), electric vehicle (EV) powertrains, power steering units, torque converters and other equipment, for which an ATF is required, which exceeds ATF Dexron III and II. Its special composition causes a longer lifetime of this liquid compared with older Dexron types. This multi-vehicle ATF meets the hardware protection of the specified low viscosity fluids, like AW-2. This product cannot be used in DCT's and CVT's or when an oil with the Ford Type F/G specification is recommended.

Specifications

Performance level:

- Aisin Warner JWS 3309 (T-IV)/ 3324(WS)/ AW-1/ AW-2
- Cat TO-2, Chrysler Dodge Mopar AS68RC/ 69RC (T-IV)
- Daihatsu ATF D-II/D-III SP
- GM Dexron VI/II/III/IV/SP-IV RR
- Hyundai/Kia SP-II/SP-III/SP-IV/SP-IV M/SP-IV RR
- Jaguar ATF 3403 M115/JLM 2023820292/
- Mazda ATF DII/M-III/M-V/FZ/A7/F-1/S-1/N-13317/
- Mitsubishi SK/SP-II/SP-III/SP-IV/AW/J2/J3/ PA/MA1
- Subaru ATF/5AT/HP
- Toyota D-II/D-III/T-III/T-IV/WS, Tesla Model S/3/X
- VW G 053 001 / G 053 025 / G 055 005 / G 055 025
- Voith 55.6335.xx (G607), Volvo 973351161540/97340/
- Allison C3/C4, BMW 7045E/8072B/LA2634/ ATF6/Mini
- Chrysler ATF+1/+2/+3, Fiat Type IV/9.55550-AV5/AV-6
- Ford Mercon/LV/M2C138-CJ/166-H/922-A1924/A/938-A
- Honda Acura DW-1/ATF-Z1(except in CVT)
- Hyundai/Kia JWS 33149638/, Isuzu ATF II/III/SP/WSI
- JASO M3151 2013-A/1A-LV/2A
- MB 236.1236.41/236.9/236.8/236.7/236.5/3/2/
- Nissan Matic C/D/J/K/P/S/W, Porsche 3403-M115/T-IV
- Suzuki ATF 33092384/2326/3317/3314/K, PSA B71 2340
- VW G 052 025 / G 052 055 / G 052 162 / G 052 990
- VW G 055 162 / G 055 540 / G 060 162
- ZF 5HP 18FL/19FL/24A/304/HP20, ML 05L/0911/A/B/21L

Typicals

Density at 15 °C, kg/l	0,845
Viscosity 40 °C, mm ² /s	29,60
Viscosity 100 °C, mm ² /s	5,90
Viscosity Index	149
Flash Point COC, °C	212
Pour Point, °C	-48