

Hypersynth 5W30

Description

A modern, synthetic, fuel economy, universal motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application

A universal, fuel economy, special composed synthetic motor oil recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans for which the most modern specifications are required.

Specifications

Performance level:

- ACEA A3/B4
- BMW Longlife-01
- Renault RN0700
- API SN/CF *)
- due to phosphorus-limit
- API SH/CF
- MB 229.3/226.5
- VW 502.00/505.00
- *) API SN quality only; not-licensable

Typicals

Density at 15 °C, kg/l	0,857
Viscosity -30 °C, mm ² /s	5870
Viscosity 40 °C, mm ² /s	72,80
Viscosity 100 °C, mm ² /s	12,15
Viscosity Index	162
Flash Point COC, °C	251
Pour Point, °C	-39
Total Base Number, mgKOH/g	10,8
Sulphate Ash, %	1,32