



Hypersynth 0W40

Description

A modern, synthetic, universal motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:

- a high and very stable viscosity index
- a high resistance against shearing
- a very fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application

A universal, special composed synthetic motor oil recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans for which the most modern specifications are required.

Specifications

Performance level:

- ACEA A3/B4
- API SN/CF
- BMW Longlife-01
- MB 229.3226.5/
- Porsche A40
- Renault RN0700/RN0710
- VW 502.00/505.00

Typicals

| | |
|--------------------------------------|-------|
| Density at 15 °C, kg/l | 0,844 |
| Viscosity -35 °C, mPa.s | 5620 |
| Viscosity 40 °C, mm ² /s | 75,90 |
| Viscosity 100 °C, mm ² /s | 13,50 |
| Viscosity Index | 183 |
| Flash Point COC, °C | 238 |
| Pour Point, °C | -48 |
| Total Base Number, mgKOH/g | 10,8 |
| Sulphate Ash, % | 1,32 |