

Tor Specialsynth GM1 5W30

Description

A modern, synthetic, fuel economy motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application

A fuel economy, special composed synthetic motor oil recommended for use in petrol engines of passenger cars. This oil is fully backward compatible with GM dexos1 Gen 2. This oil is also suitable for the PATAC requirements of China 6 emission norms.

Specifications

- API SP Resource Conserving
- ILSAC GF-6A
- Meets the requirements of:
- GM dexos 1 Gen 3
- Opel OV 040 1547 - G30
- Chrysler MS 6395
- Fiat 9.55535-CR1
- Ford WSS-M2C946-A/B1 / M2C961-A1 / M2C929-A
- GM 6094M / 4718M

Typicals

Density at 15 °C, kg/l	0,847
Viscosity -30 °C, mPa.s	3870
Viscosity 40 °C, mm ² /s	59,70
Viscosity 100 °C, mm ² /s	10,70
Viscosity Index	172
Flash Point COC, °C	222
Pour Point, °C	-39
Total Base Number, mgKOH/g	7,4
Sulphate Ash, %	0,78