

Tor Specialsynth OV 0W20

Description

A modern, synthetic, fuel economy motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- a high and very stable viscosity index
- a high resistance against shearing
- a very fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming.

Application

A modern fuel economy, special composed synthetic motor oil suitable for use in petrol and diesel engines of passenger cars and delivery vans. Specially developed for use with the specified specifications.

Specifications

Performance level:

- ACEA C5, C6
- ILSAC GF-6A
- Meets the requirements of:
- Ford WSS-M2C947-B1 / WSS-M2C962-A1
- MB 229.71 / 229.72
- Chrysler MS-12145

- API SP Resource Conserving
- Volvo VCC RBS02-AE
- Jaguar Land Rover STJLR.03.5006
- Opel OV 040 1547 A20
- Fiat 9.55535-GSX

Typicals

Density at 15 °C, kg/l	0,848
Viscosity -35 °C, mm²/s	6000
Viscosity 40 °C, mm²/s	42,60
Viscosity 100 °C, mm²/s	8,61
Viscosity Index	186
Flash Point COC, °C	224
Pour Point, °C	-45
Total Base Number, mgKOH/g	7,5
Sulphate Ash, %	0,61