



## Unifleet Ultra 15W40 TBN-16

### Description

A diesel engine oil, formulated with solvent refined base oils and a well-balanced choice of additives. This engine oil has the following properties:

- a very powerful detergency prevents deposits in the engine
- a very strong dispersion that prevents from precipitation and sludge
- a powerful activity against corrosion and foam
- a high and stable viscosity index
- a powerful activity against wear resulting in strongly reduced wear of piston-rings and cylinder-liners

### Application

This engine lubricant is applicable to diesel engines (normally- or turbo-aspirated) even under tough operation conditions and all the year round. This engine oil has a special additive system and may therefore be used, when fuels with relatively high sulphur contents are involved. This product is suitable for application in Euro 4 and Euro 5 engines.

### Specifications

Performance level:

- ACEA E7
- Cat ECF-1-a/ECF-2
- Detroit Diesel 93K215
- Global DHD-1
- Mack EO-N/EO-M Plus
- MB 228.3
- Renault VI RLD-2
- API CI-4/SL
- Cummins CES 20077/20078
- Deutz DQC III-18
- JASO DH-1
- MAN M 3275 - 1
- MTU Type 2
- Volvo VDS-3

### Typicals

Density at 15 °C, kg/l	0,885
Viscosity -20 °C, mm <sup>2</sup> /s	6300
Viscosity 40 °C, mm <sup>2</sup> /s	110,30
Viscosity 100 °C, mm <sup>2</sup> /s	14,50
Viscosity Index	135
Flash Point COC, °C	212
Pour Point, °C	-30
Total Base Number, mgKOH/g	16,1
Sulphate Ash, %	2,00