



Unifleet Ultra 20W50

Description

A gasoline- and diesel engine oil, formulated with solvent refined base oils and a wellbalanced choice of additives. This engine oil has the following properties:

- a very powerful detergency prevents deposits in the engine
- a very strong dispersion that prevents from precipitation and sludge
- a powerful activity against corrosion and foam
- a high and stable viscosity index
- a powerful activity against wear resulting in strongly reduced wear of piston-rings and cylinder-liners

Application

This engine lubricant is applicable to gasoline and diesel engines (normally- or turboaspirated) even under the toughest operation conditions and all the year round. This engine oil has a special additive system and may therefore be used, when fuels with relatively high sulphur contents are involved. This special quality of engine oil is mainly developed to allow extended oil drain intervals and to prevent «bore polishing» (=cylinder-wear) in diesel engines. This product is suitable for application in Euro 4 and Euro 5 engines.

Specifications

Performance level:

- ACEA E7
- API CI-4/SL
- Cummins CES 2007720078/
- Deutz DQC III-18
- Global DHD-1
- MB 228.3

Typicals

Density at 15 °C, kg/l	0,892
Viscosity -15 °C, mPa.s	7500
Viscosity 40 °C, mm ² /s	156,30
Viscosity 100 °C, mm ² /s	17,50
Viscosity Index	123
Flash Point COC, °C	230
Pour Point, °C	-30
Total Base Number, mgKOH/g	11,1
Sulphate Ash, %	1,43